

Press Release 16th March 2009

EnviroVent's new range provides the complete package

Meeting the demands of today's professional electrician, EnviroVent welcomes a number of new product lines for 2009, including a series of industry renowned fans with the addition of further low energy ECOWATT products. EnviroVent's Andy Makin introduces the new range of wholesale axial and centrifugal models.

With 2009's new arrivals, EnviroVent is able to offer a complete and diverse range of innovative axial and centrifugal fans to meet both domestic and commercial application requirements, all exceeding current building regulations. Incorporating the latest quality design and featuring innovative, solution-based technology with ease of installation, EnviroVent's new product lines provide the right choice for every professional electrician.

Furthermore all new products are backed by our complete service guarantee and supported by our dedicated customer service department to ensure that every customer is fully satisfied with the solution provided.

Joining the already popular SILENT range of EnviroVent's axial extract fans are the ultra-slimline and easy to install PROFILE 100 and 150 ranges of four and six inch axials suitable for bathroom and kitchen installation. Elegant and unobtrusive with a profile of down to 13mm, the range compliments any contemporary building design. The fans are fitted with sealed for life ball bearing motors and available with numerous quality features, including humidity sensors, PIR detectors and timers.

Available with a Low Watt brushless DC motor is the stylish ECOWATT PROFILE 100 model. A four inch, ultra-slimline and low energy use WC or bathroom fan for wall or ceiling installation. Covered with a 5 year guarantee and achieving an exceptionally low power consumption of only five watts, the ECOWATT PROFILE not only significantly reduces energy costs but is also easy to install and available with adjustable overrun timers and humidity sensors.

EnviroVent's bathroom range also extends to include the versatile CLASSIC 100, suitable for panel, ceiling, wall or window-mounted applications. Available in both 230V and SELV versions, the range offers a variety of optional features to include adjustable timers, humidity sensors, pullcord and integral thermoelectric shutters. The CLASSIC 100 SELV models are IP57 rated, providing total safety within the spray area of a bath and can be installed over or within zone 1.

Our expanded range of domestic centrifugal fans includes the new POWER 170 and 250 fans, suitable for bathroom and kitchen applications where higher system resistances are encountered. Fitted with powerful forward curved centrifugal impellers and automatic backdraught shutters the fans prevent air entry and limit heat leakage when the extractor is not operating. Available as two speed models, other optional features such as humidity sensors and electronic timers are also offered. The 250 versions are fitted with a convenient washable filter that can be removed safely and easily.

Mixed flow in-line fans also join EnviroVent's new domestic and commercial ranges. The MIXVENT are two-speed axial fans designed to solve ventilation problems for ducted systems. Available in six sizes from 100mm to 315mm, the low profile design makes them ideal for installations where space is restricted. Flexible location enables the fans to be connected to any point of the ventilation duct without



loss of performance, and the unique design of the support bracket allows the central cartridge, containing the motor and impeller assembly, to be fitted or removed without dismantling the ductwork.

This in-line range is also available in five low energy ECOWATT MIXVENT versions, sized to fit between 100 and 200mm ducting. Fitted with energy saving DC motor technology and covered by five year guarantees, the motors are assembled with ball bearings for enhanced working life to deliver high efficiency and low consumption. These fans are suitable for any kind of ventilation application where the fan must operate continuously, achieving significant energy savings.

The new product line-up is fully completed with the launch of the MIXVENT ROOF range, providing two-speed extract or supply roof ventilation for both domestic and commercial applications, such as restaurants, offices and car parks. All models are fitted with bird guard and base cable entry point as standard. The flexible design allows the motor and impeller casing to be simply removed by the two fixing clamps to facilitate ease of maintenance. Circular spigot coupling allows the connection to circular, rigid or flexible ducting.

With all products meeting and exceeding current building regulations and a fully backed service guarantee, today's professional electrician can install with confidence and peace of mind.

Ends

Contact G Graydon ggraydon@envirovent.com Tel + 44 (0) 1423 810810